

# RRVPA Tractor Inspection sheet

Limited 6200, Mod 6500, Open 7500, Hot Farm 9500, 6700 Superstock. 2Wd Trucks

**Tractor Name** \_\_\_\_\_

**Driver** \_\_\_\_\_

## A. Chassis

- Pass Fail** 1. Tire size and rules for class.
- Pass Fail** 2. Must have front axle skid plates or skies. Ex 2wd and Hot Farm
- Pass Fail** 3. Distance from center of rear axle to most forward part. 15' 2wd, 14' Open 13' others MAX \_\_\_\_\_
- Pass Fail** 4. Operational Brakes on rear axle.
- Pass Fail** 5. Hitch minimum 3×3¼ hole. Must be ridged in all directions. Not attached to wheelie bars.
- Pass Fail** 6. Rear Stabilizer bars. (Wheelie)
- Pass Fail** 7. Draw bar minimum 18" form center of axle to hook point.
- Pass Fail** 8. Roll Cage or ROPS and seat belt or harness.

## B. Engine

- Pass Fail** 1. Engine in proper location, with block plates. ¼ aluminum 3/16 steel.
- Pass Fail** 2. Visual check for Engine to be legal for class. (carb, heads, turbo)
- Pass Fail** 3. Fuel Tank securely mounted, check for fuel leaks. Pressurized vessels must be UL or ULC listed.
- Pass Fail** 4. Alcohol injection requires a spring on both sides of throttle plates.
- Pass Fail** 5. Headers and Stacks must extend vertically (not passed 10 degrees)
- Pass Fail** 6. Batteries must be securely mounted and covered if exposed. Master disconnect.

## C. Safety

- Pass Fail** 1. Dead man style throttle. Foot throttles must have toe strap with positive return.
- Pass Fail** 2. Operational kill switch in easy reach of Driver.
- Pass Fail** 3. Helmet and fire resistant suit, minimum 2½ pound fire extinguisher.
- Pass Fail** 4. Working rear mounted kill switch. Will be tested
- Pass Fail** 5. Neutral interlock on Started.
- Pass Fail** 6. Two Reverse indicator lights. One in rear one for the operator.
- Pass Fail** 7. Blow proof Bell housings, scatter blankets, drive shaft loops and shields.

**Notes:** \_\_\_\_\_

**Pass Fail** Is pulling unit allowed to pull at this event.

**RRVPA Inspector Signature:** \_\_\_\_\_ **Date** \_\_\_\_\_