

RRVPA Truck Inspection sheet

Prostock Superstock and Open Mod 4x4 ProStreet Diesel

Truck Name _____

Driver _____

A. Chassis

- Pass Fail** 1. Weight box no more then 60" from center of front axle. _____
- Pass Fail** 2. Must have supporting wheels on weight bar/box 6" from front 6" from ground.
- Pass Fail** 3. Wheel base length. Max 133"(Prostock 135" max) _____
- Pass Fail** 4. Operational Brakes.
- Pass Fail** 5. Hitch minimum 3x3¾ hole. must be ridged in all directions 30% of wheel base. _____ Minnimun 44" or 158" base 28%
- Pass Fail** 6. Rear Bumpers or bump stops.
- Pass Fail** 7. Prostock rear suspension must be on springs no blocks. Diesels may have blocks
- Pass Fail** 8. Tires max size 35/12.50 no modifications sipping allowed. Open must run Bar tires.

B. Engine

- Pass Fail** 1. Engine in proper location, with block plates. ¼ aluminum 1/8 steel.
- Pass Fail** 2. Visual check for Engine to be legal for class. (carb, heads, turbo casting #S)
- Pass Fail** 3. Fuel Tank securely mounted, check for fuel leaks.
- Pass Fail** 4. All vehicles running Alcohol fuel must have a yellow "A" sticker on windshield.
- Pass Fail** 5. Headers and Stacks must extend vertically. (Prostock under and pointed back)
- Pass Fail** 6. Batteries must be securely mounted not in cab of vehicle.

C. Safety

- Pass Fail** 1. Dead man style throttle.
- Pass Fail** 2. Operational kill switch in easy reach of Driver.
- Pass Fail** 3. Helmet and fire resistant suit, minimum 2½ pound fire extinguisher.
- Pass Fail** 4. Working rear mounted kill switch. Will be tested.
- Pass Fail** 5. Neutral interlock on Starter.
- Pass Fail** 6. Reverse indicator light.
- Pass Fail** 7. Blow proof Bell housings, scatter blankets, drive shaft loops and shields.

Notes: _____

Pass Fail Is pulling unit allowed to pull at this event.

RRVPA Inspector Signature: _____ **Date** _____