

9500# Hot Stock Farm

1. General Safety

1.1. Must Follow General Safety rules

A) Exceptions

- i Required Roll Cage or Factory Roll Protection Structure(ROPS)
- ii Required Ridged seat with lap belt required, High back and a 5 point harness is recommended.
- iii Required Helmet and Fire suit.

2. 9,500 lbs. maximum weight

3. Chassis

3.1. Tractors must have Hood and Grill, sheet metal to be stock length and location.

3.2. Engine and Rear-end must be of the same brand/OEM combination.

(Massy Ferguson & Perkins, Oliver & Cat/Waukesha and etc.)

3.3. Front Axle

A) Must have skid plates or ski's, unless using a factory front axle for make and model of tractor.
Fabricated axle allowed.

B) No Narrow Front axles

4. Engine

4.1. Must be OEM Block, 585 Cubic Inch Limit (Oliver2255 with Cat 3208 Allowed)

4.2. Engine must bolt directly to clutch housing or with OEM adapter.

4.3. Stock or OEM replacement 2 valve cylinder head. No overhead camshafts. OEM intake and exhaust required, no intake spacers.

4.4. Any Injection Pump, with working governor.

4.5. All Turbos must to be sealed and inspected by Fair Valley Performance (FVP) for 2026.

A) The following sealed/inspected turbos are approved RRVPA Hot Farm competition

- i S300SX-E 65mm with 2.58" inlet
- ii S300SX-R 64mm with 2.56" inlet
- iii HPT F2 6470 64mm with 2.57 inlet

B) Unsealed or broken inspection seals must be sent back FVP for inspection and seal installation

4.6. 3000 RPM Limit.

A) Must have a pig tail for sled monitor.

B) Over RPM for 1 second or more is disqualification

4.7. Dead Man Throttle not required

4.8. Diesel Fuel only, Water injection Allowed. (No Propane or NOS)

A) No Inter-coolers allowed.

5. Tires

5.1. Maximum 20.8x38 or equivalent square inch foot print.

5.2. Agriculture tire with Top cut only.